

Cirago BTA3310 Micro USB Bluetooth® 3.0 Adapter

Benefits and Features

- Micro Design - RoHS compliant
- *Bluetooth* Specification 3.0 EDR – Class 2
- Enhanced Data Rate (EDR) compliant for both 2Mbps and 3Mbps modulation modes
- Supports Read Encryption Key Size: Enables a host to determine the negotiated encryption key size to determine security requirements
- Full speed *Bluetooth* operation with full Piconet and Scatternet support
- Support for 802.11 Coexistence
- Full speed USB v 2.0 interface support OHCI and UHCI host interface
- Receiver Sensitivity -90dBm
- Stable, accurate search ability



Description	
Standard	<i>Bluetooth</i> 3.0 specification, Class 2
Chipset	CSR BC04
Operating System Support	Windows 7, Vista, XP, 2000, Mac OS 10.4.7 or above, Linux
Drivers	Motorola Driver Suite
Operating Range	10 Meters (30 feet)
Operating Frequency	2.402 GHz - 2.4835 GHz ISM Band
Connection	Point-to-Point
RF Output power	+2dBm (Class 2)
Power Supply	USB Powered
Dimensions	0.50" x 0.75" x 0.125" (unit) / 7" x 6" x 1" (Retail package)

Part number	UPC	Weight
BTA3310	858796050866	0.04 oz (unit) / 2.4 oz (retail pack)

Box Qty	Box Size
40 pcs	17" x 14" x 13"